

SAFETY DATA SHEET

Sanglier D3 Wood Adhesive

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME Sanglier D3 Wood Adhesive
SUPPLIER Sanglier Limited
Shelley Close
Lowmoor Business Park
Kirkby In Ashfield
NG17 7ET
Tel: 01623 722661
Fax: 01623 885971

2 HAZARDS IDENTIFICATION

ENVIRONMENT

The product is not expected to be hazardous to the environment.

HUMAN HEALTH

May irritate eyes.

3 COMPOSITION/INFORMATION ON INGREDIENTS

COMPOSITION COMMENTS

Water based dispersion of vinyl acetate homopolymer

4 FIRST-AID MEASURES

INHALATION

Move injured person into fresh air and keep person calm under observation. If necessary, seek hospital and bring these instructions.

INGESTION

DO NOT induce vomiting. Get medical attention immediately.

SKIN CONTACT

Remove contaminated clothing and flush with plenty of water until pain disappears. If discomfort persists transport to hospital and bring these instructions.

EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart.

5 FIRE-FIGHTING MEASURES

SPECIFIC HAZARDS

This product is waterbased and is not combustible

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Refer to section 8

ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

SPILL CLEAN UP METHODS

For waste disposal, see section 13. Large spillages should be contained and pumped into a receiving vessel. Small spillages should be absorbed on inert absorbant.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

No specific usage precautions noted.

STORAGE PRECAUTIONS

Do not use storage vessels or pipework made of aluminium, copper or their alloys. Store between +5C and 35C protected from frost and direct sunlight.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Sanglier D3 Wood Adhesive

ENGINEERING MEASURES

Provide adequate ventilation.

RESPIRATORY EQUIPMENT

If ventilation is insufficient, suitable respiratory protection must be provided.

HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

EYE PROTECTION

Goggles/face shield are recommended.

HYGIENE MEASURES

When using do not eat, drink or smoke.

SKIN PROTECTION

Wear apron or protective clothing in case of splashes.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	White		
ODOUR	Ester.		
SOLUBILITY	insoluble but miscible in all proportions		
RELATIVE DENSITY	0.9-1.1	VAPOUR PRESSURE	23hPa @20C
pH-VALUE, CONC. SOLUTION	2.5-3.5	VISCOSITY	7000-9000 mPa s
FLASH POINT (°C)	not applicable		

10 STABILITY AND REACTIVITY

STABILITY

Stable under the prescribed storage conditions.

MATERIALS TO AVOID

None

11 TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION

Long term experience of this product type indicates no danger to health when properly handled under industrial conditions.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not regarded as dangerous for the environment.

BIOACCUMULATION

The product is not bioaccumulating.

DEGRADABILITY

DOC Elimination after 2 days (OECD302B) : 98%. This product can be virtually eliminated from water by abiotic processes, eg adsorption onto activated sludge.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Waste product should not be discharged directly into drains or waterways without treatment. Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

GENERAL

This product is not classified as Dangerous for Carriage

15 REGULATORY INFORMATION

16 OTHER INFORMATION

DATE

6 November 2008

Sanglier D3 Wood Adhesive